

HF-01S

Standard Heat Flux Sensor



Overview

The HF-01S is a small size standard plate type heat flux sensor. It is an ideal option for research and engineering applications as well as manufacturing control and monitoring processes. Manufactured in compliance with standards ASTM C1046 and ISO 9869, EKO HF-10S includes a built-in thermal guard and two facings to ensure an even heat flux distribution and therefore a reliable measurement experience. The unique combination of small size, thin body, and high sensitivity, makes this sensor a perfect choice for accurate measurement of heat flux, even in low heat flux conditions. Thanks to the thin body and high thermal conductivity, the thermal resistance is kept very low to minimize the heat flux disturbance on the surface and avoid edge losses.


Features



High sensitivity



Fast response



Thin, small,
compact form
factor



Water proof
(IP67)



Durable &
versatile



Suitable for a
range of application

Explore EKO

Made in Japan for over 90 years, EKO solar energy sensors and environmental instruments are built on a legacy of innovation, an uncompromising commitment to quality, and industry-leading accuracy. With a range of products and services to suit every project or application requirement, explore EKO now, or get in touch to find out how EKO Instruments can help you.



Transducers
MC-20



LI-19 HH
Datalogger



Thermal
Conductivity
Testers



Thermal
Analysis
Instruments



Heat Flux
Sensors

Sensor Specifications

Nominal Sensitivity	50 $\mu\text{V}/\text{W}/\text{m}^2$
Time Constant (63%)	< 2 sec
Thermal Resistance	$2.3 \times 10^{-3} \text{ m}^2 \text{ K}/\text{W}$
Electric Impedance	8 Ω - 12 Ω (+10°C - +40°C)
Operating Temperature Range	-30 to 80°C, cable -20°C to +60 °C
Heat Flux Range	$\pm 10000 \text{ W}/\text{m}^2$
Temperature Dependency	0.2 %/°C
Dimensions (L x W x H)	25 x 24 x 2.0 mm
Sensing Area	91 mm ²
Guard Width	5x thickness of the sensor
Calibration Uncertainty	$\pm 3 \%$ (K=2)
Ingress Protection	IP67
Cable Dimensions	3m (Diameter: 2.1 mm)

Application

Use HF-01S to measure the heat flux from or towards a surface of interest. This helps you evaluate the insulation performance of for instance, a wall. Install the sensor on building walls, refrigeration units, insulated enclosures, and any surface where the heat transfer rate is to be determined. Installation is straightforward, but must be done correctly to ensure accurate and reliable data. Follow the Quick Start Guide and the Demonstration video to install and measure.

Check out EKO QHT-10 Thermal monitoring Kit used to monitor heat flux and temperature, equipped with a battery-powered datalogger. Experience a plug & play measurement experience.



QR

Use the QR code to visit our website, contact our team, or to find out more about the **HF-01S**, other related products, and the full range of industry- leading EKO sensors and instruments.



EKO Instruments Co. Ltd

info@eko.co.jp
+81-3-3469-6713

EKO Instruments Sales India

sales-in@eko-instruments.com
+91-98690-47721

EKO Instruments Europe B.V.

sales-eu@eko-instruments.com
+31-0-703050117

EKO Instruments Sales China

sales-cn@eko-instruments.com
+81-3-3469-6713

EKO Instruments USA Inc.

sales-usa@eko-instruments.com
+1-408-977-7751

eko-instruments.com